




- Rigid insulating Kevlar panels - solid and secure
- Packed on one pallet position - ISU-90 or 463L palletized
- Can be complexed with other ADAMS shelter variants
- 1/2 the packed volume and 3x the area vs ISO container shelters
- Extendable to any length by adding arch modules
- Patented technology - folds and deploys from compact pieces
- 4-person setup < 2 hours add 30min for HVAC/lights
- 2-person tear down/pack within ISU-90 in < 1.5 hours
- Modular design configures to shore power, generator or Trac9 Solar kits with ease
- Lighter packages which exclude standard components such as HVAC, PDU, Electrical, External Decking, Outlets, Lights are available at a discounted price upon request




- Fly sheets available in any color - scheme changes in minutes
- 120 mph wind rated when anchored to concrete
- 40psf snow load
- 60 mph rated with no additional anchoring or stakes
- Area > 650 Sqft, indefinitely extendable in 120 Sqft increments
- Temperature/humidity -controlled interior
- Supports positive and negative pressure environments
- More usable space with greater modularity vs ISO containers
- Panels reduce noise and are more efficient for hot/cold climates
- Bolt-on insulation, sound reduction, or RF shielding kits available
- Weight of ADAMS kit packed in ISU-90
 - ISU-90 1515 LBS
 - 4 arch ADAMS 4281 LBS
 - 3 arch ADAMS 3495 LBS
 - ISU + 4 arch ADAMS = 5796 LBS

ADAMS - Maintenance Shelter



Arch modules are interoperable and allow shelters to increase in size or add functions with added arches



BASE SHELTER SPECIFICATIONS

DIMENSIONS

- 32'L x 20'W x 11'H
- Floor area - >650 sqft, indefinitely extendable in 120 sqft increments.

STRUCTURE

- Composed of rigid Kevlar composite panels with a patented folding design that maximizes portability and packability.

ASSEMBLY

- **4 person setup < 2 hours, no heavy equipment required**
- Safe setup and error proof design. Shelter components are portable and keyed to set-up only one way

CAPACITY

- >15 persons for general use.
- >30 persons configured for billeting and barracks facilities.

COLOR AND OPTIONS

- Panels exterior – grey exterior and white interior - colors can be sourced per customer preference.
- Exterior fabric flysheets - simple color upgrades to any base shelter for concealment
- Capable of being upgraded with signal suppression coverings.
- Supports any type of external camouflage system
- Anchor kit provided for various surfaces and climates - no anchors are needed below 60mph winds.

WEIGHT AND TRANSPORT

- 3 arch shelter 3495 lbs
- 4 arch shelter 4281 lbs

OPTIONS AND ACCESSORIES

- Available with fabric endwalls - pack up to 3 shelters per 1 ISU-90 with fabric endwalls
- Shelter arches are interoperable - add or subtract arches to increase/decrease size.
- Side entry arch - add to create side doorway and allow complexing shelter to shelter
- Various internal mounts and connectors (monitors, racks, tables, etc)
- Advanced uses - ex: Ops Center, medical, ColPro, maintenance, paint booth, composite repair

PURCHASING

- Available via direct sole-source procurement via SBIR Phase 3 procurement process
- Sizes, accessories and configuration can be tailored for specific use-cases
- For details and pricing contact Trac9 - sales@T9Lab.com, 808.798.9730